OXYGEN, COMPRESSED

SDS reference: 097A

Revision date: 23/05/2017 Supersedes: 18/07/2016 Version: 6.0



Danger

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1. <u>1.</u> Product identifier		
Trade name	: OXYGEN, COMPRESSED	
SDS no	: 097A	
Chemical description	: OXYGEN, COMPRESSED	
	CAS-No. : 7782-44-7	
	EC-No. : 231-956-9	
	EC Index-No. : 008-001-00-8	
Registration-No.	: Listed in Annex IV / V REACH, exempted from registration.	
Chemical formula	: O2	
1.2. Relevant identified uses of the substance or mixture and uses advised against		
Relevant identified uses	 Industrial and professional. Perform risk assessment prior to use. Test gas/Calibration gas. Laboratory use. Medical applications. Contact supplier for more information on uses. 	
Uses advised against	: Consumer use.	
1.3. Details of the supplier of the safety data	sheet	
Company identification		

1.4. Emergency telephone number

No additional information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]			
Physical hazards	Oxidising Gases, Category 1	H270	

Gases under pressure : Compressed gas H280

2.2. Label elements

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

OXYGEN, COMPRESSED

SDS reference: 097A

Revision date: 23/05/2017 Supersedes: 18/07/2016 Version: 6.0

Labelling according to Regulation	n (EC) No. 1272/2008 [CLP]
Hazard pictograms (CLP)	GHS03 GHS04
Signal word (CLP)	: Danger
e ()	C C
Hazard statements (CLP)	: H270 - May cause or intensify fire; oxidizer.
	H280 - Contains gas under pressure; may explode if heated.
Precautionary statements (CLP)	
-	- Prevention : P220 - Keep away from combustible materials. P244 - Keep valves and fittings free from oil and grease.
	- Response : P370+P376 - In case of fire: stop leak if safe to do so.
	- Storage : P403 - Store in a well-ventilated place.
2.3. Other hazards	

: None.

SECTION 3: Composition/information on ingredients

3.1. Substances

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
OXYGEN, COMPRESSED	(CAS-No.) 7782-44-7 (EC-No.) 231-956-9 (EC Index-No.) 008-001-00-8 (Registration-No.) *1	100	Ox. Gas 1, H270 Press. Gas (Comp.), H280

Contains no other components or impurities which will influence the classification of the product.

*1: Listed in Annex IV / V REACH, exempted from registration.

*2: Registration deadline not expired.

*3: Registration not required: Substance manufactured or imported < 1t/y.

Full text of H-statements see section 16.

3.2. Mixtures : Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures - Inhalation : Remove victim to uncontaminated area. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped. - Skin contact : Adverse effects not expected from this product. - Eye contact : Adverse effects not expected from this product. - Ingestion : Ingestion is not considered a potential route of exposure. 4.2. Most important symptoms and effects, both acute and delayed Most important symptoms and effects, both acute and delayed

OXYGEN, COMPRESSED

SDS reference: 097A

Revision date: 23/05/2017 Supersedes: 18/07/2016 Version: 6.0

: Continuous inhalation of concentrations higher than 75% may cause nausea, dizziness, respiratory difficulty and convulsion. Refer to section 11.

4.3. Indication of any immediate medical attention and special treatment needed

: None.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media - Unsuitable extinguishing media	: Water spray or fog. : Do not use water jet to extinguish.
5.2. Special hazards arising from the substan	ce or mixture
Specific hazards	: Supports combustion. Exposure to fire may cause containers to rupture/explode.
Hazardous combustion products	: None.
5.3. Advice for firefighters	
Specific methods	 Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems. If possible, stop flow of product. Use water spray or fog to knock down fire fumes if possible. Move containers away from the fire area if this can be done without risk.
Special protective equipment for fire fighters	 Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask. Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

	 Try to stop release. Evacuate area. Monitor concentration of released product. Eliminate ignition sources. Ensure adequate air ventilation. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Act in accordance with local emergency plan. Stay upwind. 	
6.2. Environmental precautions		
	: Try to stop release.	
6.3. Methods and material for containment and cleaning up		
	: Ventilate area.	
6.4. Reference to other sections		
	: See also sections 8 and 13.	

SECTION 7: Handling and storage

7.1. Precautions for safe handling

OXYGEN, COMPRESSED

SDS reference: 097A

Revision date: 23/05/2017 Supersedes: 18/07/2016 Version: 6.0

Safe use of the product	 The product must be handled in accordance with good industrial hygiene and safety procedures. Only experienced and properly instructed persons should handle gases under pressure. Consult supplier for specific recommendations. Consider pressure relief device(s) in gas installations. Ensure the complete gas system was (or is regularily) checked for leaks before use. Do not smoke while handling product. Keep equipment free from oil and grease. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Use only oxygen approved lubricants and oxygen approved sealings. Use only with equipment cleaned for oxygen service and rated for cylinder pressure. Do not breathe gas. Avoid release of product into atmosphere.
Safe handling of the gas receptacle	 Know heats of product the cathlogatete. Suck back of water into the container must be prevented. Open valve slowly to avoid pressure shock. Refer to supplier's container handling instructions. Do not allow backfeed into the container. Protect cylinders from physical damage; do not drag, roll, slide or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. If user experiences any difficulty operating cylinder valve discontinue use and contact supplier. Never attempt to repair or modify container valves or safety relief devices. Damaged valves should be reported immediately to the supplier. Keep container valve outlets clean and free from contaminants particularly oil and water. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to transfer gases from one cylinder/container to another. Never use direct flame or electrical heating devices to raise the pressure of a container. Do not remove or deface labels provided by the supplier for the identification of the cylinder contents. Containers should be stored in the vertical position and properly secured to prevent them from falling over.
7.2. Conditions for safe storage, including a	ny incompatibilities
	 Observe all regulations and local requirements regarding storage of containers. Containers should not be stored in conditions likely to encourage corrosion. Container valve guards or caps should be in place. Containers should be stored in the vertical position and properly secured to prevent them from falling over. Stored containers should be periodically checked for general condition and leakage. Keep container below 50°C in a well ventilated place. Segregate from flammable gases and other flammable materials in store. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible materials.

7.3. Specific end use(s)

: None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

OEL (Occupational Exposure Limits) : No data available.

DNEL (Derived-No Effect Level) : No data available.

PNEC (Predicted No-Effect Concentration) : No data available.

8.2. Exposure controls

OXYGEN, COMPRESSED

SDS reference: 097A

Revision date: 23/05/2017 Supersedes: 18/07/2016 Version: 6.0

8.2.1. Appropriate engineering controls	
	 Provide adequate general and local exhaust ventilation. Systems under pressure should be regularily checked for leakages. Ensure exposure is below occupational exposure limits (where available). Avoid oxygen rich (>23,5%) atmospheres. Gas detectors should be used when oxidising gases may be released. Consider the use of a work permit system e.g. for maintenance activities.
8.2.2. Individual protection measures, e.g. per	sonal protective equipment
	 A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered: Wear suitable hand, body and head protection. Wear goggles with suitable filter lenses when use is cutting/welding. PPE compliant to the recommended EN/ISO standards should be selected.
Eye/face protection	: Wear safety glasses with side shields. Standard EN 166 - Personal eye-protection - specifications
Skin protection	
- Hand protection	: Wear working gloves when handling gas containers. Standard EN 388 - Protective gloves against mechanical risk.
- Other	 Consider the use of flame resistant safety clothing. Standard EN ISO 14116 - Limited flame spread materials. Wear safety shoes while handling containers. Standard EN ISO 20345 - Personal protective equipment - Safety footwear.
Respiratory protection	: None necessary.
Thermal hazards	: None necessary.
8.2.3. Environmental exposure controls	
	: None necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	
Physical state at 20°C / 101.3kPa	: Gas.
Colour	: Colourless.
Odour	: No odour warning properties.
Odour threshold	: Odour threshold is subjective and inadequate to warn of overexposure.
pH value	: Not applicable.
Molar mass	: 32 g/mol
Melting point	: -219 °C
Boiling point	: -183 °C
Flash point	: Not applicable for gases and gas mixtures.
Critical temperature [°C]	: -118 °C
Evaporation rate (ether=1)	: Not applicable for gases and gas mixtures.
Flammability range	: Non flammable.
Vapour pressure [20°C]	: Not applicable.
Vapour pressure [50°C]	: Not applicable.
Relative density, gas (air=1)	: 1.1
Relative density, liquid (water=1)	: 1.1
Solubility in water	: 39 mg/l

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

OXYGEN, COMPRESSED

SDS reference: 097A

Revision date: 23/05/2017 Supersedes: 18/07/2016 Version: 6.0

Partition coefficient n-octanol/water [log Kow]	: Not applicable for inorganic gases.	
Auto-ignition temperature	: Not applicable.	
Viscosity [20°C]	: Not applicable.	
Explosive Properties	: Not applicable.	
Oxidising Properties	: Oxidiser.	
- Coefficient of oxygen equivalency (Ci)	: 1	
9. <u>2.</u> Other information		
Other data	: Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.	

SECTION 10: Stability and reactivity

10.1. Reactivity	
	: No reactivity hazard other than the effects described in sub-sections below.
10. <u>2.</u> Chemical stability	
	: Stable under normal conditions.
10.3. Possibility of hazardous reactions	
	: Violently oxidises organic material.
10.4. Conditions to avoid	
	: None under recommended storage and handling conditions (see section 7).
10.5. Incompatible materials	
	 Keep equipment free from oil and grease. Consider the potential toxicity hazard due to the presence of chlorinated or fluorinated polymers in high pressure (> 30 bar) oxygen lines in case of combustion. May react violently with combustible materials. May react violently with reducing agents. For additional information on compatibility refer to ISO 11114.
10.6. Hazardous decomposition products	
	: None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects	
Acute toxicity	: No known toxicological effects from this product.
Skin corrosion/irritation	: No known effects from this product.
Serious eye damage/irritation	: No known effects from this product.
Respiratory or skin sensitisation	: No known effects from this product.
Germ cell mutagenicity	: No known effects from this product.
Carcinogenicity	: No known effects from this product.
Toxic for reproduction : Fertility	: No known effects from this product.
Toxic for reproduction : unborn child	: No known effects from this product.
STOT-single exposure	: No known effects from this product.
STOT-repeated exposure	: No known effects from this product.
Aspiration hazard	: Not applicable for gases and gas mixtures.

SECTION 12: Ecological information

12.1. Toxicity

Assessment

: No ecological damage caused by this product.

OXYGEN, COMPRESSED

SDS reference: 097A

Revision date: 23/05/2017 Supersedes: 18/07/2016 Version: 6.0

EC50 48h - Daphnia magna [mg/l] EC50 72h - Algae [mg/l] LC50 96 h - Fish [mg/l]	No data available. No data available. No data available.
12.2. Persistence and degradability	
Assessment	: No ecological damage caused by this product. No data available.
12.3. Bioaccumulative potential	
Assessment	: No ecological damage caused by this product.
12. <u>4.</u> Mobility in soil	
Assessment Assessment	: No data available. : No ecological damage caused by this product.
12.5. Results of PBT and vPvB assessment	
Assessment	: Not classified as PBT or vPvB.
12. <u>6.</u> Other adverse effects	
Effect on the ozone layer	: None.
Effect on global warming	: None.
SECTION 13: Disposal considerations	

13.1. Waste treatment methods

	Contact supplier if guidance is required. May be vented to atmosphere in a well ventilated place. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from local regulations or operating permits are not exceeded. Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at http://www.eiga.org for more guidance on suitable disposal methods.
List of hazardous waste codes (from Commission Decision 2001/118/EC) 13.2. Additional information	: 16 05 04 *: Gases in pressure containers (including halons) containing dangerous substances.
15.2. Additional mormation	: None.

SECTION 14: Transport information

<u>14.1. UN number</u>	
UN-No.	: 1072
14. <u>2.</u> UN proper shipping name	
Transport by road/rail (ADR/RID)	: OXYGEN, COMPRESSED
Transport by air (ICAO-TI / IATA-DGR)	: Oxygen, compressed
Transport by sea (IMDG)	: OXYGEN, COMPRESSED
14. <u>3.</u> Transport hazard class(es)	
Labelling	

2.2 : Non-flammable, non-toxic gases 5.1 : Oxidizing substances

OXYGEN, COMPRESSED

SDS reference: 097A

Revision date: 23/05/2017 Supersedes: 18/07/2016 Version: 6.0

Transport by road/rail (ADR/RID)	
Class	: 2
Classification code	: 10
Hazard identification number	: 25
Tunnel Restriction	: E - Passage forbidden through tunnels of category E
Transport by air (ICAO-TI / IATA-DGR)	
Class / Div. (Sub. risk(s))	: 2.2 (5.1)
Transport by sea (IMDG)	
Class / Div. (Sub. risk(s)) Emergency	: 2.2 (5.1)
Schedule (EmS) - Fire Emergency	: F-C
Schedule (EmS) - Spillage	: S-W
14.4. Packing group	
Transport by road/rail (ADR/RID)	: Not applicable
Transport by air (ICAO-TI / IATA-DGR)	: Not applicable
Transport by sea (IMDG)	: Not applicable
14.5. Environmental hazards	
Transport by road/rail (ADR/RID)	: None.
Transport by air (ICAO-TI / IATA-DGR)	: None.
Transport by sea (IMDG)	: None.
14.6. Special precautions for user	
Packing Instruction(s)	
Transport by road/rail (ADR/RID)	: P200
Transport by air (ICAO-TI / IATA-DGR)	
Passenger and Cargo Aircraft	: 200
Cargo Aircraft only	: 200
Transport by sea (IMDG)	: P200
Special transport precautions	 Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: Ensure there is adequate ventilation. Ensure that containers are firmly secured. Ensure cylinder valve is closed and not leaking. Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
14.7. Transport in bulk according to Annex I	I of MARPOL 73/78 and the IBC Code

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

OXYGEN, COMPRESSED

SDS reference: 097A

Revision date: 23/05/2017 Supersedes: 18/07/2016 Version: 6.0

Seveso Directive : 2012/18/EU (Seveso III)	: Listed. Covered.
National regulations	
National legislation	: Ensure all national/local regulations are observed.
Water hazard class (WGK)	: -
Kenn-Nr.	: 743
15.2. Chemical safety assessment	
	: A CSA does not need to be carried out for this product.

SECTION 16: Other information

Indication of changes	: Revised safety data sheet in accordance with commission regulation (EU) No 2015/830.
Training advice	: Ensure operators understand the hazard of oxygen enrichment. Receptacle under pressure.
Further information	: This Safety Data Sheet has been established in accordance with the applicable European Union legislation. Classification in accordance with the calculation methods of Regulation (EC) 1272/2008 CLP.

Full text of H- and EUH-statements

Ox. Gas 1	Oxidising Gases, Category 1
Press. Gas (Comp.)	Gases under pressure : Compressed gas
H270	May cause or intensify fire; oxidizer
H280	Contains gas under pressure; may explode if heated

DISCLAIMER OF LIABILITY

: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.